

*Reliable Rainfall  
Measurement*



Model 52202

**Tipping Bucket Rain Gauge**

*The YOUNG Tipping Bucket Rain Gauge meets the specifications of the World Meteorological Organization (WMO).*

The design uses a proven tipping bucket mechanism for simple and effective rainfall measurement. The bucket geometry and material are specially selected for maximum water release, thereby reducing contamination and errors.

Catchment area of 200 cm<sup>2</sup> and measurement resolution of 0.1 mm meet the recommendations of the WMO. Extensive use of molded thermo-



plastic components ensures maximum performance and value. Leveling screws and bullseye level are built-in for easy and precise adjustment in the field. Measured precipitation is discharged through a collection tube for verification of total rainfall. Model 52202 is heated for operation in cold temperatures. An unheated version, 52203, is available for use in moderate climates.



## Specifications

<b>Size:</b>	18 cm dia. x 30 cm high, (39 cm high with mounting base)
<b>Catchment Area:</b>	200 cm <sup>2</sup>
<b>Resolution:</b>	0.1 mm per tip
<b>Accuracy:</b>	2% up to 25 mm/hr 3% up to 50 mm/hr
<b>Output:</b>	Magnetic reed switch (N.O.), rating 24VAC/DC 500mA
<b>Operating Temperature:</b>	-20°C to +50°C (heated)
<b>Power:</b>	18 Watts for heater only
<b>Mounting:</b>	Clamp for 1" (1.34" dia.) iron pipe or 3 bolts on 160mm dia. circle
<b>Other:</b>	Leveling adjustment, thermostatic control for heater, intake screen

## Ordering Information

## MODEL

TIPPING BUCKET RAIN GAUGE (HEATED) .....	52202
TIPPING BUCKET RAIN GAUGE (UNHEATED) .....	52203



Nexgen  
Axiom House, Station Road,  
Stroud, Gloucestershire, U.K.  
TEL: +44 (0) 1453 759 408 FAX: +44 (0) 1453 759 416  
E-mail: info@nexgenwind.com  
Web Site: www.nexgenwind.com